

Safety Check List Opti 2023 Zespri AIMS Games

Competitor: _____

Sail Number: _____

Hulls	In good seaworthy condition	
Life Jacket	Good condition and correct size for sailors' weight.	
Whistle	Attached to the life jacket (no 'pea' whistles)	
Sail Numbers	Min 50mm high on each side of the hull near the transom Sail numbers must match the hull numbers. Numbers must be clearly visible from both sides.	
Towline	In good condition 5mm minimum diameter & minimum 7metres in length measured from the bow of the boat to end of towline including loop	
Bailer	Min 1 litre capacity attached to boat by a lanyard	
Air Bags	All 3 must be firmly inflated and obviously able to hold air. Each airbag must be well secured by 3 straps	
Rudder:	The rudder retaining clip (to keep the rudder secured to the transom) in good working order	
Dagger Board	Has a lanyard attachment to prevent floating away in capsize	
Mast tied in:	The mast must be securely tied to the hull by either line or collar (check collar is fully operational?) Tape is not acceptable.	
Bridle/Mainsheet:	Gap of no greater than 100mm from the boom at any point (to prevent head entrapment)	
Bridle/Mainsheet connection:	Must be shackle type device, capable of easy/quick release. Screw pins or tying with line is not acceptable.	
Bridle/Mainsheet disconnection: for quick release	Must not be self-opening or able to snag on clothing, life jacket or towline. Must have a short cord attached	
Beach Trolley	Must have sail number on Trolley	

Signature of checker: _____

